



An
Employee
Owned
Company

Portable Electric

Direct Drive – DHS Series

Blast away greasy residue and tough debris with these heavy-duty pressure washers.



DH-2003-SE0E2M

PUMP

- Equipped with Mi-T-M Pressure Relief Start (Mi-T-M pump models)
- Direct drive triplex piston pump with ceramic plungers
- Factory preset unloader

MOTOR

- Totally enclosed fan-cooled electric motor
- 35-foot power cord

FRAME

- Reinforced powder coated steel frame with center balanced lift
- 13-inch flat-free tires

COMPONENTS

- Energy-efficient top-fired heat exchanger
- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)

MISCELLANEOUS

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 225°F

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch steel wire-braided high pressure hose with quick connects
- Adjustable pressure insulated dual lance with trigger gun

LIMITED WARRANTY

- 1 year electric motor

CERTIFICATION

- ETL Certified – US and Canada

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	PLUG TYPE	BURNER FUEL TANK CAPACITY	BURNER FUEL CONSUMPTION	BTU PER HOUR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DH-1002-SE0E1G	1000	2.0	1.5 HP, 120V, 1Ø, 15.0A	General	NEMA 5-15P	4.0 gallons	1.33 gph	186,000	43x29.5x36.5in.	418 lb.	295 lb.
DH-1002-SE0E1M*	1000	2.0	1.5 HP, 120V, 1Ø, 15.0A	Mi-T-M	NEMA 5-15P	4.0 gallons	1.33 gph	186,000	43x29.5x36.5in.	410 lb.	237 lb.
DH-1502-SE0E1G	1500	2.0	2.0 HP, 120V, 1Ø, 19.0A	General	NEMA 5-20P	4.0 gallons	1.21 gph	169,000	43x29.5x36.5in.	422 lb.	299 lb.
DH-1502-SE0E1M*	1500	2.0	2.0 HP, 120V, 1Ø, 19.0A	Mi-T-M	NEMA 5-20P	4.0 gallons	1.21 gph	169,000	43x29.5x36.5in.	414 lb.	291 lb.
DH-2003-SE0E2G	2000	2.8	4.0 HP, 230V, 1Ø, 18.0A	General	NEMA 6-20P	4.0 gallons	1.48 gph	207,200	43x29.5x36.5in.	439 lb.	316 lb.
DH-2003-SE0E2M*	2000	2.8	4.0 HP, 230V, 1Ø, 18.0A	Mi-T-M	NEMA 6-20P	4.0 gallons	1.48 gph	207,200	43x29.5x36.5in.	431 lb.	308 lb.

*Model does not include float tank and high pressure detergent injector.

Portable Electric

Hot Water – Direct Drive – DHS Series

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector – High pressure water mixes with detergent to clean even the heaviest build-up	All models
850-0433	50-foot x 3/4-inch hose – For when you need extra hose for added mobility	All models

OPTIONS: *Options must be ordered with unit and cannot be added later.*

PART NUMBER	DESCRIPTION	FITS MODELS
HX-0232*	300°F steam – Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-1002-SE0E1G
HX-0233	Adjustable thermostat – Operator is able to adjust outlet water temperature between 86°-248°F	DH-2003 models
HX-0235	Hour meter – Displays the number of hour unit has been in operation	All models
HX-0237	Auto start/stop – When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	DH-1002-SE0E1M
HX-0238	Time delay shutdown – Timer will shut unit off automatically when trigger gun is released and timer reaches setting	DH-1002-SE0E1M
HX-0239*	300°F steam – See HX-0232 for description	DH-1002-SE0E1M
HX-0240*	300°F steam – See HX-0232 for description	DH-2003-SE0E2G
HX-0241*	300°F steam – See HX-0232 for description	DH-2003-SE0E2M
HX-0243	Auto start/stop – See HX-0237 for description	DH-2003 models
HX-0244	Time delay shutdown – See HX-0238 for description	DH-2003 models
HX-0245*	300°F steam – See HX-0232 for description	DH-1502-SE0E1M
HX-0246*	300°F steam – See HX-0232 for description	DH-1502-SE0E1G
HX-0275	Auto start/stop – See HX-0237 for description	DH-1502-SE0E1M
HX-0276	Time delay shutdown – See HX-0238 for description	DH-1502-SE0E1M
HX-0308	Adjustable thermostat – Operator is able to adjust outlet water temperature between 86°-248°F	DH-1002 & DH-1502 models

*Includes adjustable thermostat.



NEMA 5-15P,
15-amp plug



NEMA 5-20P,
20-amp plug



NEMA 6-20P,
20-amp plug



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.